

Hayfield

54"/ TYPE II / 20 oz.

LOW VOC **RECYCLED CONTENT**

PHYSICAL PROPERTIES

Weight	20 oz. PLY/620 G/PLM	13.3 oz. PSY/451 G/PSM
Width	54"/137 cm	
Backing	Osnaburg	
Match	Reverse, random	

Custom colors, weights, recycled backing and micro venting available

Meets or exceeds Federal Specification CCC-W-408D

FIRESAFETY

- Class "A" Fire rated - Tested in accordance with ASTM E-84 Tunnel Test
- Passes Class "A" NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test

See website or contact us for additional results

ENVIRONMENT&HEALTH

- **Contains 10% recycled content**
- **Meets California section 01350 IAQ test requirements for wallcovering**
- **Can contribute to LEED EQ 4.1 for low emitting materials, adhesives, and sealants, if used with low VOC adhesives**
- **Can contribute to LEED MR 5.1 for regional materials**

ANTIMICROBIAL FEATURES

Bolta® wallcoverings contain antimicrobial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls. All Bolta® wallcoverings can be perforated, with a 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

WARRANTY

5 year warranty against manufacturing defects. Additional information is available at www.boltawallcovering.com