

# genon

## Tailored Twill

54" / TYPE II / 20 oz.

LOW VOC RECYCLED CONTENT

### PHYSICAL PROPERTIES

Weight 20 oz. PLY/620 G/PLM 13.3 oz. PSY/451 G/PSM

Width 54"/137 cm

Backing Osnaburg

Reverse, random

Custom colors, weights, and micro venting available

Meets or exceeds Federal Specification CCC-W-408D

### FIRE SAFETY

- Class "A" Fire rated – Tested in accordance with ASTM E-84 Tunnel Test
- Passes Class "A" NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test
- Tested in accordance with CAN/ULC S102.2

See website or contact us for additional results

### ENVIRONMENT & HEALTH

- Low VOC, California section 01350 IAQ
- 10% Recycled content
- Non-Phthalate
- EPD/HPD
- California Prop 65, no labeling required

### CLEANABILITY

- Inherent anti-microbial protection
- Withstands hospital-grade cleaners & disinfectants
- Available as a custom with **INVISICAP** | complete **chemical** protection

### WARRANTY

5 year warranty against manufacturing defects. Additional information is available at [genonwallcovering.com](http://genonwallcovering.com)



 Render Ready Tiles available

**W2-TW-10** NEUTRAL WEFT