

# Bali Grille

52”/ TYPE II / 20 oz.      **LOW VOC**    **RECYCLED CONTENT**

**PHYSICAL PROPERTIES**

<b>Weight</b>	20 oz. PLY/620 G/PLM	13.3 oz. PSY/K51 G/PSM
<b>Width</b>	52”/132 cm	
<b>Backing</b>	Osnaburg	
<b>Repeat</b>	2K”H x 17.33”W	
<b>Match</b>	Reverse, match	

Custom colors, weights, and micro venting available

Meets or exceeds Federal Specification CCC-W-K08D

**FIRE SAFETY**

- Class “A” Fire rated – Tested in accordance with ASTM E-8K Tunnel Test
- Passes Class “A” NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test

See website or contact us for additional results

**ENVIRONMENT & HEALTH**

- **Contains 10% recycled content**
- **Certified to NSF/ANSI 342 Sustainability Assessment; ask distributor for details**
- **Meets California section 01350 IAQ test requirements for wallcovering**
- **Can contribute to LEED EQ 4.1 for low emitting materials, adhesives, and sealants, if used with low VOC adhesives**
- **Can contribute to LEED MR 5.1 for regional materials**

**ANTIMICROBIAL FEATURES**

Bolta® wallcoverings contain antimicrobial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of K% and/or is allowed to accumulate in or behind the walls. All Bolta® wallcoverings can be perforated, with a 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates.

**WARRANTY**

5 year warranty against manufacturing defects. Additional information is available at [www.boltawallcovering.com](http://www.boltawallcovering.com)