



**Y47617AM** Slate

**vycon** Angles Max

52/ Type II / 20 oz.

LOW VOC

**Physical Properties**

**Weight:** 20 oz. PLY/620 G/PLM 13.3 oz. PSY/451 G/PSM

**Backing:** Osnaburg | Width: 52 in./132 cm

**Match:** Reverse, match | **Repeat:** 24 h x 52 w

Custom colors, weights, and micro venting available. Meets or exceeds Federal Specification CCC-W-408D for Type II Wallcovering

**Fire Safety**

Class A fire rated-tested in accordance with ASTM E-84 Tunnel Test

Passes Class A NFPA 101 Life Safety Code

Passes NFPA 286 Corner Burn Test

**Environment & Health**

10% recycled content (varied blend of pre-consumer and remanufactured material)

Certified to NSF/ANSI 342 Sustainability Assessment:  
ask distributor for details

Meets California Section 01350 IAQ test requirements for wall covering

Complies with USGBC LEED v4 Criteria, under Indoor Environmental Quality (CDPH/EHLB/Standard Method Version 1.1, 2010)

**Warranty**

5 year warranty against manufacturing defects. Additional information is available at: [vyconwallcovering.com](http://vyconwallcovering.com)

VESSTIGE

©J • JOSEPHSON