

PHILLIP JEFFRIES

NATURAL | TEXTURED | SPECIALTY | WALLCOVERINGS

HANGING INSTRUCTIONS

VINYL SAVILE SUITING WALLCOVERINGS

STOP: DO NOT CUT OR INSTALL UNTIL YOU HAVE READ THESE INSTRUCTIONS!

Thank you for choosing this fine handcrafted wallcovering. For the best results, we believe that a professional wallcovering installer should hang these wallcoverings.

DESCRIPTION:

The custom fashions of Savile Row in textile-inspired plain, pinstripe, and plaid, now available in VINYL - merging luxe design with the durability and technology offered by today's performance wallcoverings.

PREPARATION:

Before you cut and hang, please be sure you have:

1. The correct wallcovering and the correct amount of wallcovering to finish the job.
2. Inspect the wallcovering carefully to ensure it is free of defects:
If no defect is evident before installation, the material should be inspected after three (3) strips are installed. If any defect is evident at this time (or at any point in the installation) no additional material should be hung until Phillip Jeffries is notified. **NO CLAIMS WILL BE ALLOWED FOR MORE THAN (3) STRIPS ON THE WALL.** All claims must be made within 30 days of the invoice date. No labor claims will be allowed at any time.

BUILDING & MATERIAL CONDITIONS: The building must be weather-tight with HVAC settings (including pressure, temperature and relative humidity) the same as those of an occupied building for three days prior to, throughout installation and three days after installation. The walls must be structurally sound including elimination of sources of moisture accumulation into the wall or wall cavity. The wallcovering must be in a clean and dry condition and must be stored at normal occupied building temperature and humidity for at least three days prior to installation. All adhesives and primers must be new, good quality, commercial grade materials, which have not been contaminated.

IF YOU HAVE ANY QUESTIONS, PLEASE STOP AND CONTACT
PHILLIP JEFFRIES BEFORE PROCEEDING.

WALL PREPARATION:

1. The walls to be covered must be properly prepared to insure that the wallpaper will adhere to the wall surface. Even the strongest adhesive can only work when the wall surface is clean and properly prepared.
2. Phillip Jeffries recommends that installers use a hard, acrylic, pigmented, wall-protecting primer that is SPECIFICALLY made for WALLCOVERING INSTALLATION and WALL PROTECTION.
DO NOT USE R-35.
3. Allow the primer to dry thoroughly before hanging.

PHILLIP JEFFRIES

NATURAL | TEXTURED | SPECIALTY | WALLCOVERINGS

HANGING INSTRUCTIONS

VINYL SAVILE SUITING WALLCOVERINGS

STOP: DO NOT CUT OR INSTALL UNTIL YOU HAVE READ THESE INSTRUCTIONS!

INSTALLATION

ADHESIVE

1. We recommend a clay based adhesive.
2. Whip clay with paste beater and use full strength. If paste container has already been opened, make sure that no dried flakes fall in. Apply the paste to the back of the paper using a pasting machine, or for hand application a short napped paint roller.

TRIMMING

1. The edges are untrimmed and will require cutting a precision edge on your work table or by MAKING A DOUBLE CUT ON THE WALL to create as fine a seam as possible.
2. Trim edges with a VERY sharp razor blade. Change your blades often.

MATCHING FOR PINSTRIPE AND PLAID ITEMS

1. Pinstripe Items #2138-2145: 1" (2.54 cm.) H.
Plaid Items #2146-2153: 2" (5.08 cm.) V x 2" (5.08 cm.) H
2. Once a precision edge is cut, seams should be butted together to create a straight match.

TIPS

1. All strips should be hung in sequence, as they come off the roll.
2. Install each sheet on the wall using a short bristle brush or flexible broadknife.
3. Apply material above doors and windows as it comes off the roll, DO NOT SKIP.
4. Remove excess adhesive and dirt from wallcovering surface and seams immediately, using a clean sponge or damp cloth frequently rinsed in clean, warm water.
5. All vinyl wallcoverings should be washed regularly to prevent dirt and grime from accumulating. Depending on traffic (light, medium, heavy), vinyl should be washed two or three times a year.
6. Ordinary dirt can be removed with mild soap and warm water. Dry wallcovering with a soft, lint-free cloth or towel. For more difficult stains that are only surface deep, the use of a stronger detergent is recommended. WE RECOMMEND ALL CLEANERS BE TESTED IN AN INCONSPICUOUS AREA TO INSURE COMPATIBILITY WITH THE WALLCOVERING.