

A Cord To Adore

54" / TYPE II / 20 oz. **LOW VOC** **RECYCLED CONTENT**

PHYSICAL PROPERTIES

Weight 20 oz. PLY/620 G/PLM 13.3 oz. PSY/451 G/PSM
Width 54"/137 cm
Backing Osnaburg
Match Reverse, random

Custom colors, weights and micro venting available

Meets or exceeds Federal Specification CCC-W-408D

FIRE SAFETY

- Class "A" Fire rated – Tested in accordance with ASTM E-84 Tunnel Test
- Passes Class "A" NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test
- Tested in accordance with CAN/ULC S102.2

See website or contact us for additional results

ENVIRONMENT & HEALTH

- 10% recycled content (varied blend of pre-consumer and remanufactured material)
 - Certified to NSF/ANSI 342 Sustainability Assessment: ask distributor for details
 - Meets California section 01350 IAQ test requirements for wallcovering
 - Complies with USGBC LEED v4 Criteria, under Indoor Environmental Quality (CDPH/EHLB/Standard Method Version 1.1, 2010)
-

WARRANTY

5 year warranty against manufacturing defects.

Additional information is available at genonwallcovering.com
