



inVinci **Altair** pattern meets or exceeds all Type II requirements of CCC-W-408D and W-101.

## **PERFORMANCE SPECIFICATIONS**

Weight (Avg):	20 oz (452 gr/m <sup>2</sup> )
Width:	52-54" (132/137 cm)
Backing:	Non-Woven (Mylar)
Installation:	Straight Hang / Straight Across Match
	Repeat: V: 17.66" H: 17.66"

## **FIRE SAFETY**

ASTM-E84 (GRC) Class A  
NFPA 101 Life Safety Code

## **ENVIRONMENTAL AND HEALTH**

Phthalate Free  
Health Product Declaration  
Environmental Product Declaration  
Meets State of Washington Building Specification for Indoor Air Quality  
Meets California Section 01350 Indoor Air Quality Standard  
Aggressive manufacturing materials recovery and reuse program  
Highly cleanable water-based inks  
Free of PBDE's (Brominated Flame Retardants)

## **USGBC LEED SUPPORT**

Support USGBC LEED v4.1 Criteria  
Materials and Resources; Building Product Disclosure and Optimization  
(Includes Recycled Content; Construction Waste Management; HPD's)  
Indoor Environmental Quality; Low-Emitting Materials

## **MOISTURE, MOLD, AND MILDEW**

Vinyl wallcovering functions as a vapor barrier. If water or moisture becomes trapped between the wallcovering and the wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use of vinyl wallcovering.

A mildew inhibiting agent has been added to help protect against fungal and other microbiological growth. No additives however, will prevent mold growth if moisture is allowed to accumulate and its sources are not eliminated. Further protection against mold growth may be achieved by Permavent®, a unique microventing technology that literally "breathes," helping manage the mobile moisture in walls.

## **WARRANTY**

inVinci is guaranteed to be free of defeats in workmanship and material for five years. For additional details on moisture management, Permavent®, warranty and other inVinci innovations, visit our website at [invinciwallcoverings.com](http://invinciwallcoverings.com).