



inVinci **Anoka** pattern meets or exceeds all Type II requirements of CCC-W-408D and W-101.

PERFORMANCE SPECIFICATIONS

Weight (Avg):	20 oz (452 gr/m ²)
Width:	52/54" (132/137 cm)
Backing:	Osnaburg
Installation:	Reverse Hang / Random Match

FIRE SAFETY

Class A – ASTM E-84 (GRC)
Passes NFPA 286 Corner Burn
NFPA 101 Life Safety Code
BS476 Class 0
CAN-ULC S102
EN13501 (B-S1-d0)

ENVIRONMENTAL AND HEALTH

Phthalate Free
Health Product Declaration
Environmental Product Declaration
Meets State of Washington Building Specification for Indoor Air Quality
Meets California Section 01350 Indoor Air Quality Standard
Aggressive manufacturing materials recovery and reuse program
Highly cleanable water-based inks
Free of PBDE's (Brominated Flame Retardants)

USGBC LEED SUPPORT

Support USGBC LEED v4.1 Criteria
Materials and Resources; Building Product Disclosure and Optimization
(Includes Recycled Content; Construction Waste Management; HPD's)
Indoor Environmental Quality; Low-Emitting Materials

MOISTURE, MOLD, AND MILDEW

Vinyl wallcovering functions as a vapor barrier. If water or moisture becomes trapped between the wallcovering and the wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use of vinyl wallcovering.

A mildew inhibiting agent has been added to help protect against fungal and other microbiological growth. No additives however, will prevent mold growth if moisture is allowed to accumulate and its sources are not eliminated. Further protection against mold growth may be achieved by Permavent®, a unique microventing technology that literally “breathes,” helping manage the mobile moisture in walls.

WARRANTY

inVinci is guaranteed to be free of defeats in workmanship and material for five years. For additional details on moisture management, Permavent®, warranty and other inVinci innovations, visit our website at invinciwallcoverings.com.