



8 Colorways:	PL21-01 Tundra	PL21-05 Bluff*
	PL21-02 Mesa	PL21-06 Dune
	PL21-03 Path	PL21-07 Trail
	PL21-04 Cliff	PL21-08 Cavern*

*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Woven (Osnaburg)	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II

NFPA 101® Life Safety Code®

Fire Testing	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹
	- Class A Rating - Flame Spread - 10 - Smoke Developed - 5
	NFPA 286 Corner Burn Test ²
	- Meets requirements for Flame Spread, Smoke Developed, & Flashover

¹ When applied to GRC board with A-848-B adhesive ² When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011
-------------------------	--

Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices
---------------------------	--

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association
©2023 Koroseal Interior Products, LLC.