

genon

Island Weave

54" / TYPE II / 20 oz.

LOW VOC RECYCLED CONTENT

PHYSICAL PROPERTIES

Weight 20 oz. PLY/620 G/PLM 13.3 oz. PSY/451 G/PSM
Width 54"/137 cm
Backing Osnaburg
Match Reverse Random

Custom colors, weights, and micro venting available

Meets or exceeds Federal Specification CCC-W-408D

FIRE SAFETY

- Class "A" Fire rated – Tested in accordance with ASTM E-84 Tunnel Test
- Passes Class "A" NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test
- Tested in accordance with CAN/ULC S102.2

See website or contact us for additional results

ENVIRONMENT & HEALTH

- Low VOC, California section 01350 IAQ
- 10% Recycled content
- Non-Phthalate
- EPD/HPD
- California Prop 65, no labeling required

CLEANABILITY

- Inherent anti-microbial protection
- Withstands hospital-grade cleaners & disinfectants
- Available as a custom with **INVISICAP** | complete chemical protection

WARRANTY

5 year warranty against manufacturing defects. Additional information is available at genonwallcovering.com



 Render Ready Tiles available

W2-DV-08 STRAW